

PMC Engineering, LLC

11 Old Sugar Hollow Road, Danbury, CT 06810 U.S.A Tel: (203) 792-8686 Fax: (203) 743-2051 Website: www.pmc1.com Email: sales@pmc1.com

PMC LEGACY SERIES Ordering Code

Electronic Flush Mount (original patent) Transmitter, SAN Design

PMC Configurator

Part Number		PT/EL-SAN	XXX XX XX	
Model Construction				
Ranges	0 - 5"WC through 0 - 300 psi	g	XXX	
	±5"WC through ±400"WC compound - cermaic diaphragm onl	У		
0 - 3"H	Ig through 0 - 30"Hg Vacuum (Negative) -ceramic diaphragm onl	у		
	0 - 15 psia through 0 - 150 psia - ceramic diaphragm onl	У		
Other pressure units and ranges can be specified: PSI, Pa, kPa, Bar, mbar, kg/cm ² , mm/Hg.				
Diaphragm	Hastelloy C - Standar	d	Нс	
	All Hasteloy C wetted parts; Diaphragm and Retainer Rin	g	Sp	
	Ceramic - suitable for high abrasives and ranges below 40"W	С	CER/L	
	Ceramic - suitable for Vacuum, Absolute and Compound range	S	CER/V	
Termination	Stainless Steel cover with 10' vented polyurethane cable		CV/P	
	Stainless Steel cover with 10' FEP cable (chemical resistant))	CV/T	
	Terminal Junction Head, Flip Top design, Anodized Aluminun	n	TH	
Terminal June	ction Head, Flip Top design, Anodized Aluminum with LCD Displa	•	TH/D	
	Terminal Junction Head, 316L Stainless Stee	el	TH/SS	
	Terminal Junction Head, 316L Stainless Steel with LCD Displa		TH/SS/D	
Electrical Connectio	n to Sensor - CV version Polyurethane molded cable, per			
	FEP cable assembly, per f			
Remote Electronics				RE/xx'
Specify ca	ble length between Sensor Assembly and Electronic Termination			
Remote option includes stainless steel mounting bracket				
Process Connections: Specify desired process connection, NOT INCLUDED with Transmitter.				
	PMC Flush Mount Weld on Nipple, SAN Design 316L S			
PMC NPT Male Process connection Adapters 1" or 1½" LT-07-SAN-S (x")				
For Complete Process Connections and Flange listings please see Process Connections, Tools and Accessories page				
*Higher Accuracy: Most Ranges are available for upgrade to 0.1% accuracy. Consult PMC for availability				
	For operations in hazardous environments			
*Contact factory for custom Connections and Reducers.				
Example Ordering Format: PMC - PT/EL-SAN - XXX - Hc - CV/P				