



Ordering Information

Dip Stick - Level Probe Transmitters

MODEL: PT/EL DS

PMC Electronic Transmitter with Stainless Steel Dip Stick Level Probe

Standard order code is shown below. Special options follow.

ORDER CODE: **PMC - PT/EL DS - XXX - CER - CV/P (XX')**

Ranges:	0 to 5" WC through 0 to 300 PSI	_____		
Diaphragm:	Cer/L	Ceramic, Standard diaphragm for Dip Stick Level Probe transmitter	_____	
Termination:	CV/P	* Stainless Steel Cover with 3 meters vented polyurethane cable.	_____	XXX
	CV/T	* Stainless Steel Cover with 3 meters Tefzel (chemical resistant) cable.		XXX
	TH	** Terminal Junction Head, Aluminum Anodized		XXX
	TH/D	** Terminal Junction Head, Aluminum Anodized with LCD Display		XXX
	TH-SS	** Terminal Junction Head, 316L Stainless Steel		XXX
	TH-SS/D	** Terminal Junction Head, 316L Stainless Steel with LCD Display		XXX

Dip Stick Assembly: Specify length of 316L Stainless Steel tube required. **(XX') xxx per foot**
One piece standard lengths are 18", 2', 4', 6' and 8' (.150" wall thickness, 1 1/32" O. D. tube).
For combination lengths i.e. 12' (4' plus 8') add **xxx for each joint kit required**.

NOTE: The Dip Stick Level Probe model PT/EL DS incorporates a 1 1/2" ceramic diaphragm with the sensor housing assembly on this model measuring 1.60" O.D.

* Vented Cable: Polyurethane (Standard) - xxx per meter. / Tefzel (Chemical Resistant) - xxx per meter.

** Add "G" to the end of the order code - Gland Nut, 1/2" Nylon liquid tight cord connector (terminal head accessory) - additional xxx

MODEL: MIN PT/EL DS

PMC Miniature Electronic Transmitter with Stainless Steel Dip Stick Level Probe

Standard order code is shown below. Special options follow.

ORDER CODE: **PMC - MIN PT/EL DS - XXX - CER - CV/P (XX')**

Ranges:	0 to 10" WC through 0 to 300 PSI	_____		
Diaphragm:	Cer/L	Ceramic, Standard diaphragm for Dip Stick Level Probe transmitter	_____	
Termination:	CV/P	* Stainless Steel Cover with 3 meters vented polyurethane cable.	_____	XXX
	CV/T	* Stainless Steel Cover with 3 meters Tefzel (chemical resistant) cable.		XXX
	TH	** Terminal Junction Head, Aluminum Anodized		XXX
	TH/D	** Terminal Junction Head, Aluminum Anodized with LCD Display		XXX
	TH-SS	** Terminal Junction Head, 316L Stainless Steel		XXX
	TH-SS/D	** Terminal Junction Head, 316L Stainless Steel with LCD Display		XXX

Dip Stick Assembly: Specify length of 316L Stainless Steel tube required. **(XX') xxx per foot**
One piece standard lengths are 18", 2', 4', 6' and 8' (.150" wall thickness, 1 1/32" O. D. tube).
For combination lengths i.e. 12' (4' plus 8') add **xxx for each joint kit required**.

NOTE: The Miniature Dip Stick Level Probe model MIN PT/EL DS incorporates a 1" ceramic diaphragm with the sensor housing assembly on this model measuring 1 1/32" O.D.

* Vented Cable: Polyurethane (Standard) - xxx per meter. / Tefzel (Chemical Resistant) - xxx per meter.

** Add "G" to the end of the order code - Gland Nut, 1/2" Nylon liquid tight cord connector (terminal head accessory) - additional xxx

FOB: Danbury, CT USA • Prices are subject to change without notice • PMC® is not responsible for printing or pricing errors.

PROCESS MEASUREMENT & CONTROLS, INC

11 OLD SUGAR HOLLOW ROAD, DANBURY, CT 06810 TEL: (203) 792-8686 TOLL-FREE: (800) 869-5747



Ordering Information *Smart Dip Stick - Level Probe Transmitters*

MODEL: SMT/EL DS

PMC SMART Electronic Transmitter with Stainless Steel Dip Stick Level Probe (HART® Protocol)

Standard order code is shown below. Special options follow.

ORDER CODE:	PMC - SMT/EL - DS - XXX - CER - CV/P		(XX')
Ranges:	0 to 5" WC through 0 to 300 PSI		
Diaphragm:	Cer/L	Ceramic, Standard diaphragm for Dip Stick Level Probe transmitter	
Termination:	CV/P	* Stainless Steel Cover with 3 meters vented polyurethane cable.	XXX
	CV/T	* Stainless Steel Cover with 3 meters Tefzel (chemical resistant) cable.	XXX
	TH	** Terminal Junction Head, Aluminum Anodized	XXX
	TH/D	** Terminal Junction Head, Aluminum Anodized with LCD Display	XXX
	TH-SS	** Terminal Junction Head, 316L Stainless Steel	XXX
	TH-SS/D	** Terminal Junction Head, 316L Stainless Steel with LCD Display	XXX

Dip Stick Assembly: Specify length of 316L Stainless Steel tube required. **(XX') xxx per foot**
*One piece standard lengths are 18", 2', 4', 6' and 8' (.150" wall thickness, 1 1/32" O. D. tube).
 For combination lengths i.e. 12' (4' plus 8') add xxx for each joint kit required.*

NOTE: The Dip Stick Level Probe model SMT PT/EL DS incorporates a 1 1/2" ceramic diaphragm with the sensor housing assembly on this model measuring 1.60" O.D.

* Vented Cable: Polyurethane (Standard) - xxx per meter. / Tefzel (Chemical Resistant) - xxx per meter.

** Add "G" to the end of the order code - Gland Nut, 1/2" Nylon liquid tight cord connector (terminal head accessory) - additional xxx

MODEL: SMT - MIN/EL DS

PMC SMART Miniature Electronic Transmitter with Stainless Steel Dip Stick Level Probe (HART® Protocol)

Standard order code is shown below. Special options follow.

ORDER CODE:	PMC - SMT - MIN/EL DS - XXX - CER - CV/P		(XX')
Ranges:	0 to 10" WC through 0 to 300 PSI		
Diaphragm:	Cer/L	Ceramic, Standard diaphragm for Dip Stick Level Probe transmitter	
Termination:	CV/P	* Stainless Steel Cover with 3 meters vented polyurethane cable.	XXX
	CV/T	* Stainless Steel Cover with 3 meters Tefzel (chemical resistant) cable.	XXX
	TH	** Terminal Junction Head, Aluminum Anodized	XXX
	TH/D	** Terminal Junction Head, Aluminum Anodized with LCD Display	XXX
	TH-SS	** Terminal Junction Head, 316L Stainless Steel	XXX
	TH-SS/D	** Terminal Junction Head, 316L Stainless Steel with LCD Display	XXX

Dip Stick Assembly: Specify length of 316L Stainless Steel tube required. **(XX') xxx per foot**
*One piece standard lengths are 18", 2', 4', 6' and 8' (.150" wall thickness, 1 1/32" O. D. tube).
 For combination lengths i.e. 12' (4' plus 8') add xxx for each joint kit required.*

NOTE: The Miniature Dip Stick Level Probe model SMT MIN PT/EL DS incorporates a 1" ceramic diaphragm with the sensor housing assembly on this model measuring 1 1/32" O.D.

* Vented Cable: Polyurethane (Standard) - xxx per meter. / Tefzel (Chemical Resistant) - xxx per meter.

** Add "G" to the end of the order code - Gland Nut, 1/2" Nylon liquid tight cord connector (terminal head accessory) - additional xxx

FOB: Danbury, CT USA ▪ Prices are subject to change without notice ▪ PMC® is not responsible for printing or pricing errors.

PROCESS MEASUREMENT & CONTROLS, INC
 11 OLD SUGAR HOLLOW ROAD, DANBURY, CT 06810 TEL: (203) 792-8686 TOLL-FREE: (800) 869-5747