



Ordering Information

Pneumatic Transmitters

MODEL: LT/DR

PMC Level Transmitter

Includes a PMC® 316L Stainless Steel Weld-on Nipple.

Standard order code is shown below. Special options follow.

ORDER CODE: **PMC - LT/DR - XXX" - N - Ha - S**

Ranges: 0 to 300" Water Column is standard
¹ Other ranges: 0-10, 0-25, 0-50, 0-100 and 0-500" WC
0-20, 0-30, 0-60, and 0-100 PSIG

*Other pressure units and ranges can be specified.
Examples: PSI, Pa, kPa, Bar, mbar, etc.*

Vacuum Ranges must be ordered with Sanitary Connections: LT/SAN (Page ORDLTSAN506)

O-Rings:	N	Buna N is standard — Good to 200° F	
	Si	Silicone — Good to 400° F	extra xxx
	V	Viton — Good to 400° F	extra xxx
	EPR	Ethylene Propylene — Resistant to Solvents	extra xxx

Diaphragm:	Ha	Havar is standard — Good for Corrosion and Vibration resistance	
	Hc	Hastelloy C — Caustic and Acid Resistant	extra xxx
	Ta	Tantalum — Chemical and High Temperature resistant	extra xxx

Temperature:	S	Standard Temperature Range - Good to 200° F	
	HT	High Temperature feature - Good to 400° F	xxx

Additional charge for high temperature is included above under Silicone or Viton O-Rings.

Options:

Stainless Steel Adapters:
PMC Standard Transmitters are equipped with chrome plated brass adapters. Stainless Steel adapters upgrade are available. **extra xxx**

Hastelloy C Upgrade: Retainer Ring and Diaphragm with Viton O-Rings **extra xxx**

Barbed Exhaust (LT-BE): Exhaust fitting **extra xxx**

Matched Pairs, for match ranging each unit:
This includes a clip-on rotameter to monitor air supply continuously. **extra xxx per unit**

¹ Pneumatic Level Transmitters calibrated to ranges under 50" water column - additional charge xxx

PROCESS CONNECTIONS:

Nipples:	LT-07	PMC® 316L Stainless Steel Flush Mount Weld-on Nipple Included	
	LT-07-S	Threaded Nipple with 1½" NPTM	extra xxx

(See page ORDPC506 for complete Process Connection listing)

Note: Custom Connections and Reducers are also available, consult factory.

Additional Notes:

FOB: Danbury, CT USA ▪ Prices are subject to change without notice ▪ PMC is not responsible for printing or pricing errors.

PROCESS MEASUREMENT & CONTROLS, INC

11 OLD SUGAR HOLLOW ROAD, DANBURY, CT 06810 TEL: (203) 792-8686 TOLL-FREE: (800) 869-5747



Ordering Information

Pneumatic Transmitters

MODEL: LT/SAN

PMC Sanitary Level Transmitter

Includes a PMC® 316L Stainless Steel Sanitary Weld-on Nipple.

Standard order code is shown below. Special options follow.

ORDER CODE:

PMC - LT/SAN - XXX - Si - Ha - HT

Ranges:	0 to 300" Water Column is standard. _____			
	¹ Other ranges: 0-10, 0-25, 0-50, 0-100 and 0-500" WC 0-20, 0-30, 0-60, and 0-100 PSIG			
	<i>Other pressure units and ranges can be specified. Examples: PSI, Pa, kPa, Bar, mbar, etc.</i>			
	For Vacuum Ranges, Consult Factory - additional charge xxx			
O-Rings:	Si	Silicone is standard — Good to 400° F _____		
	V	Viton — Good to 400° F		
	EPR	Ethylene Propylene — Resistant to Solvents		
Diaphragm:	Ha	Havar — Good for Corrosion and Vibration resistance _____		
	Hc	Hastelloy C — Caustic and Acid Resistant	extra xxx	
	Ta	Tantalum — Chemical and High Temperature resistant	extra xxx	
Temperature:	HT	High Temperature Pneumatic Transmitter Configuration _____ Includes Silicone O-Rings and Teflon® Face Seal Ring (Good to 400° F)		xxx
Options:	Stainless Steel Adapters: PMC Standard Transmitters are equipped with chrome plated brass adapters. Stainless Steel adapters upgrade are available. extra xxx			
	Hastelloy C Upgrade: Retainer Ring and Diaphragm with Viton O-Rings extra xxx			
	Barbed Exhaust (LT-BE): Exhaust fitting extra xxx			
	Matched Pairs , for match ranging each unit: This includes a clip-on rotameter to monitor air supply continuously. extra xxx per unit			

¹ Pneumatic Level Transmitters calibrated to ranges under 50" water column - additional charge **xxx**

PROCESS CONNECTIONS:

Nipples:	LT-07-SAN	PMC® Stainless Steel Sanitary Flush Mount Weld-on Nipple Included	
	LT-07-SAN-TC2	2" Tri Clamp® Nipple 316L Stainless Steel	extra xxx
	LT-07-SAN-TC2-HC	2" Tri Clamp® Nipple in Hastelloy C	extra xxx
Flanges:	LT-SAN FMS	316L Stainless Steel, 150# Flange Mounted Adapters, PMC® Sanitary design	
	LT-SAN FM PVC	PVC Flange Mounted Adapters, with PMC® Sanitary design	

(See page **ORDPC506** for complete Process Connection listing)

Note: Custom Connections and Reducers are also available, consult factory.

Additional Notes:

FOB: Danbury, CT USA ▪ Prices are subject to change without notice ▪ PMC is not responsible for printing or pricing errors.

PROCESS MEASUREMENT & CONTROLS, INC

11 OLD SUGAR HOLLOW ROAD, DANBURY, CT 06810 TEL: (203) 792-8686 TOLL-FREE: (800) 869-5747