



Ordering Information

Electronic Transmitters

MODEL: MIN/S SAN

PMC Slimline Electronic Sanitary Transmitter

Standard order code is shown below. Special options follow.

(OPTION)

ORDER CODE:

PMC - MIN/S - SAN - XXX - Cer - CV/P (DIN / x)

Ranges:	0 to 10" WC through 0 to 300 PSIG ± 10" WC through ± 400" WC Compound 0 to 3" Hg through 0 to 30" HG Vacuum (Negative) 0 to 30 PSIA through 0 to 150 PSIA <i>Other pressure units and ranges can be specified. Examples: PSI, Pa, kPa, Bar, mbar, kg/cm², mm/Hg, etc.</i>			
Diaphragm:	Cer/L Ceramic (for Pressure and Level ranges) Cer/V Ceramic (for Vacuum and Absolute ranges)		extra	xxx
Termination:	CV/P * Stainless Steel Cover with 3 meters vented polyurethane cable. CV/T * Stainless Steel Cover with meters Tefzel (chemical resistant) cable. CV/D Stainless Steel Cover with Aluminum LCD Display housing . NOTE: LCD Display version comes with DIN 4-pole male connection installed.			xxx xxx xxx
DIN PLUG QUICK CONNECT: (OPTION)	Add " DIN / S " (Straight Connector) or " DIN / A " (Angled Connector) to the end of above order code for DIN plug connector (4-pole) DIN Plug Connector option			extra xxx

* Additional Vented Cable: Polyurethane (Standard) - xxx per ft. / Tefzel (Chemical Resistant) - xxx per ft.

PROCESS CONNECTIONS: Specify desired process connection. Nipple is **not included** in transmitter order code.

Nipples:	PT-07-SAN PMC® 316L Stainless Steel Sanitary Flush Mount Weld-on Nipple PT-07-SAN-TC1 1 / 1½" Tri Clamp® Nipple 316L Stainless Steel PT-07-SAN-S Sanitary Threaded Nipple with 1/2" or 1" NPTM	xxx xxx xxx
Flanges:	PT-SAN FMS 316L Stainless Steel, 150# Flange Mounted Adapters with Sanitary nipple design PT-SAN FM PVC PVC Flange Mounted Adapters, with PMC® Sanitary design	

(See page **ORDPC506** for complete Process Connection and Flange listing)

Note: Custom Connections and Reducers are also available, consult factory.

Additional Notes:

FOB: Danbury, CT USA ▪ Prices are subject to change without notice ▪ PMC is not responsible for printing or pricing errors.

PROCESS MEASUREMENT & CONTROLS, INC
11 OLD SUGAR HOLLOW ROAD, DANBURY, CT 06810 TEL: (203) 792-8686 TOLL-FREE: (800) 869-5747

ORDMINSSAN506



Ordering Information

Electronic Transmitters

MODEL: MIN/S

PMC Slimline Electronic O-Ring Transmitter

O-Ring Process Connection version, Standard order code is shown below. Special options follow.

(OPTION)

ORDER CODE: PMC - MIN/S - XXX - Cer - CV/P (DIN / x)

Ranges: 0 to 10" WC through 0 to 150 PSIG
Other pressure units and ranges can be specified.
Examples: PSI, Pa, kPa, Bar, mbar, etc.

For ranges over 150 PSIG, Vacuum and Absolute see **MIN/S SAN (Slimline Sanitary)**

Diaphragm: Cer/L Ceramic (for Pressure and Level ranges)

Termination: CV/P * Stainless Steel Cover with 3 meters vented polyurethane cable. **xxx**

CV/T * Stainless Steel Cover with 3 meters **Tefzel (chemical resistant)** cable. **xxx**

CV/ D * Stainless Steel Cover with Aluminum LCD Display housing. **xxx**

NOTE: LCD Display version comes with DIN 4-pole male connection installed.

DIN PLUG QUICK CONNECT: Add "DIN / S" (Straight Connector) or "DIN / A" (Angled Connector) to the end of above order code for DIN plug connector (4-pole)
(OPTION)

DIN Plug Connector option **extra xxx**

* Additional Vented Cable: Polyurethane (Standard) - xxx per ft. / Tefzel (Chemical Resistant) - xxx per ft.

PROCESS CONNECTIONS: Specify desired process connection. Nipple is **not included** in transmitter order code.

Nipples: PT-07 PMC® 316L Stainless Steel Flush Mount Weld-on Nipple **xxx**
PT-07-S Threaded Nipple with ½" or 1" NPTM **xxx**

(See page **ORDPC506** for complete Process Connection and Flange listing)

Note: Custom Connections and Reducers are also available, consult factory.

Additional Notes:

FOB: Danbury, CT USA ▪ Prices are subject to change without notice ▪ PMC is not responsible for printing or pricing errors.

PROCESS MEASUREMENT & CONTROLS, INC
11 OLD SUGAR HOLLOW ROAD, DANBURY, CT 06810 TEL: (203) 792-8686 TOLL-FREE: (800) 869-5747