



# Ordering Information

Seal Gauges

**MODEL: SGB**

## PMC Seal Gauges

Includes a PMC® 316L Stainless Steel Weld-on Nipple.

Standard order code is shown below. Special options follow.

### ORDER CODE:

**PMC - SGB - XXX - V - Hc - S**

#### Ranges:

0 to 100 PSI is standard. \_\_\_\_\_

Other ranges: 0-15, 0-30, 0-60, and 0-200 PSI  
 0-100, 0-200, 0-400, 0-700 and 0-1400 kPa  
 0-1, 0-2, 0-4, 0-6 and 0-7 Bar  
 0-1, 0-2, 0-4, 0-7, 0-14 and 0-20 kg/cm<sup>2</sup>

<sup>1</sup> Low range of 0 to 15 PSI, 0 to 100 kPa and 0 to 1 kg/cm<sup>2</sup> - additional charge  
 For ranges over 200 PSI and 1400 kPa see **Sanitary Seal Gauges**

#### O-Rings:

**V** Viton O Ring is standard - Good to 400° F \_\_\_\_\_

#### Diaphragm:

**Hc** Hastelloy C diaphragm is standard - Corrosion, Caustic and Acid Resistant \_\_\_\_\_

#### Temperature:

**S** Standard Temperature Range - Good to 400° F \_\_\_\_\_

**xxx**

#### Options:

**Back Connected:** Transmitter and connections with rear mount **extra xxx**

<sup>1</sup> Seal Gauges calibrated to 0 to 15 PSIG - additional charge **xxx**

### PROCESS CONNECTIONS:

#### Nipples:

**LT-07**

PMC® 316L Stainless Steel Flush Mount **Weld-on Nipple Included**

**LT-07-S**

Threaded Nipple with 1½" NPTM

**extra xxx**

**(See ORDPC506 for complete Process Connection listing)**

**Note: Custom Connections and Reducers are also available, consult factory.**

Additional Notes:

FOB: Danbury, CT USA ▪ Prices are subject to change without notice ▪ PMC is not responsible for printing or pricing errors.

**PROCESS MEASUREMENT & CONTROLS, INC**

11 OLD SUGAR HOLLOW ROAD, DANBURY, CT 06810 TEL: (203) 792-8686 TOLL-FREE: (800) 869-5747

ORDSGB506



# Ordering Information

Seal Gauges

**MODEL: SGB SAN**

## PMC Sanitary Seal Gauges

PMC includes a 316L Stainless Steel Sanitary Weld-on Nipple with each Sanitary Seal Gauge order

Standard order code is shown below. Special options follow.

### ORDER CODE:

**PMC - SGB SAN - XXX - V - Hc - S**

#### Ranges:

0 to 100 PSI is standard. \_\_\_\_\_

Other ranges: 0-15, 0-30, 0-60, 0-200, 0-300, and 0-400 PSI  
 0-100, 0-200, 0-400, 0-700, 0-1400 and 0-2000 kPa  
 0-1, 0-2, 0-4, 0-6 and 0-7 Bar  
 0-1, 0-2, 0-4, 0-7, 0-14 and 0-20 kg/cm<sup>2</sup>

<sup>1</sup> Low range of 0 to 15 PSI, 0 to 100 kPa and 0 to 1 kg/cm<sup>2</sup> - additional charge  
 (Vacuum Ranges, Consult Factory additional **xxx**)

#### O-Rings:

**V** Viton O Ring is standard - Good to 400° F \_\_\_\_\_

#### Diaphragm:

**Hc** Hastelloy C diaphragm is standard - Corrosion, Caustic and Acid Resistant \_\_\_\_\_

#### Temperature:

**S** Standard Temperature Range - Good to 400° F \_\_\_\_\_

**xxx**

#### Options:

**Back Connected:** Transmitter and connections with rear mount **extra xxx**

<sup>1</sup> Seal Gauges calibrated to 0 to 15 PSIG - additional charge **xxx**

### PROCESS CONNECTIONS:

#### Nipples:

**LT-07-SAN** PMC® Stainless Steel Sanitary Flush Mount **Weld-on Nipple Included**

**LT-07-SAN-TC2** 2" Tri Clamp® Nipple 316L Stainless Steel **extra xxx**

**LT-07-SAN-TC2-HC** 2" Tri Clamp® Nipple in Hastelloy C **extra xxx**

**LT-07-SAN-S** Threaded Nipple with 1/2", 1" or 1 1/2" NPTM **extra xxx**

#### Flanges:

**LT-SAN FMS** 316L Stainless Steel, 150# Flange Mounted Adapters, PMC® Sanitary design

**LT-SAN FM PVC** PVC Flange Mounted Adapters, with PMC® Sanitary design

(See page **ORDPC506** for complete Process Connection and Flange listing)

**Note: Custom Connections and Reducers are also available, consult factory.**

Additional Notes:

FOB: Danbury, CT USA ▪ Prices are subject to change without notice ▪ PMC is not responsible for printing or pricing errors.

**PROCESS MEASUREMENT & CONTROLS, INC**

11 OLD SUGAR HOLLOW ROAD, DANBURY, CT 06810 TEL: (203) 792-8686 TOLL-FREE: (800) 869-5747

ORDSGBSAN506