



Ordering Information

SMART Submersible Transmitters

MODEL: SMT/EL SUB

PMC SMART Submersible Electronic Transmitter (HART® Protocol)

Standard order code is shown below. Special options follow.

ORDER CODE: PMC - SMT- PT/EL - XXX - Ha - CV/P SUB

Ranges:	¹ 0 to 5" WC through 0 to 300 PSIG		
	<i>Other pressure units and ranges can be specified. Examples: PSI, Pa, kPa, Bar, mbar, etc.</i>		
Diaphragm:	Ha Havar is standard diaphragm material - Good corrosion resistance		
	Hc Hastelloy C—Caustic and acid resistant	extra	xxx
	Cer/L Ceramic (<i>suitable for Below 40" WC Ranges</i>)	extra	xxx
Termination:	CV/P-SUB * Stainless Steel Cover with 3 meters vented polyurethane cable.		xxx
	CV/T-SUB * Stainless Steel Cover with 3 meters Tefzel (corrosion resistant) cable		xxx

¹ Ranges below 40" WC only available with ceramic diaphragm
 * Additional Vented Cable: Polyurethane (Standard) - xxx per meter. / Tefzel (Chemical Resistant) - xxx per meter.

MODEL: SMT/EL SUB RE

PMC SMART Submersible Electronic Transmitter (HART® Protocol) REMOTE

Submersible Electronic Transmitters with Separate Electronic Termination

Standard order code is shown below, Special options follow.

ORDER CODE: PMC - SMT- PT/EL - XXX - Ha - CV/P SUB RE (XX M)

Ranges:	¹ 0 to 5" WC through 0 to 300 PSIG		
	<i>Other pressure units and ranges can be specified. Examples: PSI, Pa, kPa, Bar, mbar, etc.</i>		
Diaphragm:	Ha Havar is standard diaphragm material — Good corrosion resistance		
	Hc Hastelloy C — Caustic and acid resistant	extra	xxx
	Cer/L Ceramic (<i>suitable for Below 40" WC Ranges</i>)	extra	xxx
Termination:	CV/P-SUB RE * Stainless Steel Cover with 3 meters vented polyurethane cable.		xxx
	CV/T-SUB RE * Stainless Steel Cover with 3 meters Tefzel (chemical resistant) cable.		xxx
	TH-SUB RE ** Terminal Junction Head, Aluminum Anodized		xxx
	TH/D-SUB RE ** Terminal Junction Head, Aluminum Anodized with LCD Display		xxx
	TH-SS-SUB RE ** Terminal Junction Head, 316L Stainless Steel		xxx
	TH-SS/D SUB RE ** Terminal Junction Head, 316L Stainless Steel with LCD Display		xxx

* **(xx M)** Specify length and type of cable needed between Sensor and Electronics housing, 18 M maximum. — Remote Electronic, **includes** stainless steel housing mounting bracket.

¹ Ranges below 40" WC only available with ceramic diaphragm
 * Vented Cable: Polyurethane (Standard) - xxx per meter. / Tefzel (Chemical Resistant) - xxx per meter.
 ** Add "G" to the end of the order code - Gland Nut, 1/2" Nylon liquid tight cord connector (terminal head accessory) - additional xxx

FOB: Danbury, CT USA • Prices are subject to change without notice • PMC® is not responsible for printing or pricing errors.

PROCESS MEASUREMENT & CONTROLS, INC
 11 OLD SUGAR HOLLOW ROAD, DANBURY, CT 06810 TEL: (203) 792-8686 TOLL-FREE: (800) 869-5747