



**PMC Engineering, LLC**

11 Old Sugar Hollow Road, Danbury, CT 06810 U.S.A

Tel: (203) 792-8686 Fax: (203) 743-2051

Website: www.pmc1.com Email: sales@pmc1.com

**PMC LEGACY SERIES Ordering Code**

**Pneumatic Flush-Mount Level Transmitter**

**PMC Configurator**

Part Number	LT/DR	XXX	X	Xx	X
<b>Model Construction</b>	316L Stainless Steel				
<b>Ranges</b>	0 to 300"WC - Standard		<b>XXX</b>		
	Other ranges: 0-10, 0-25, 0-50, 0-100, and 0-500"WC 0-20, 0-3-, 0-60, and 0-100 PSI <i>Other pressure units and ranges can be specified. Ex: PSI, Pa, kPa, Bar, mbar</i>				
<b>O-Rings</b>	Buna N is standard - Good to 200°F		<b>N</b>		
	Silicone - Good to 400°F		<b>Si</b>		
	Viton - Good to 400°F		<b>V</b>		
	Ethylene Propylene - Resistant to Solvents		<b>EPR</b>		
	Kalrez DR		<b>KR</b>		
<b>Diaphragm</b>	Hastelloy C - Standard		<b>Hc</b>		
	All Hasteloy wetted parts; Diaphragm and Retainer Ring		<b>Sp</b>		
	Titanium - Caustic and Acid Resistant		<b>Ti</b>		
	Tantalum - Chemical and High Temperature Resistant		<b>Ta</b>		
<b>Temperature</b>	Standard Temperature Range - Good to 200°F		<b>S</b>		
	High Temperature feature - Good to 400°F		<b>HT</b>		
	<i>See Silicone or Viton O-Rings for additional charge to high temperature</i>				
<b>Options</b>	Matched Pairs, for match ranging each unit add per unit <i>This includes a clip-on rotameter to monitor air supply continuously</i> Pneumatic Level Transmitters calibrated to ranges under 50"WC Barbed Exhaust				
<b>Process Connections:</b>	316L Stainless Steel Flush Mount Weld-on Nipple included <b>LT-07</b> 316L Stainless Steel Threaded Nipple with 1 1/2" NPTM <b>LT-07-S</b>				
<b>Dummy Plug:</b>	Stainless Steel Dummy Plug for PMC LT-07 <b>LT-11-SS</b> <i>*Contact factory for custom Connections and Reducers.</i>				
<b>Example Ordering Format: PMC -LT/DR - 300"WC - N - Hc - S</b>					