



**PMC Engineering, LLC**

11 Old Sugar Hollow Road, Danbury, CT 06810 U.S.A

Tel: (203) 792-8686 Fax: (203) 743-2051

Website: www.pmc1.com Email: sales@pmc1.com

**PMC LEGACY SERIES Ordering Code**

**Pneumatic SAN Flush-Mount Level Transmitter**

**PMC Configurator**

<b>Part Number</b>		LT/SAN	XXX	Xx	Xx	HT
<b>Model Construction</b>	316L Stainless Steel					
<b>Ranges</b>	0 to 300"WC - Standard		<b>XXX</b>			
	Other ranges: 0-10, 0-25, 0-50, 0-100, and 0-500"WC					
	0-20, 0-3-, 0-60, and 0-100 PSI					
	<i>Other pressure units and ranges can be specified. Ex: PSI, Pa, kPa, Bar, mbar</i>					
<b>O-Rings</b>	Silicone - Good to 400°F		<b>Si</b>			
	Viton - Good to 400°F		<b>V</b>			
	Ethylene Propylene - Resistant to Solvents		<b>EPR</b>			
	Kalrez		<b>KR</b>			
<b>Diaphragm</b>	Hastelloy C - Standard		<b>Hc</b>			
	Hastelloy C Retainer: Hastelloy C Retainer Ring upgrade					
	Titanium - Caustic and Acid Resistant		<b>Ti</b>			
	Tantalum - Chemical and High Temperature Resistant		<b>Ta</b>			
<b>Temperature</b>	High Temperature Pneumatic Transmitter configuration					<b>HT</b>
	Includes Silicone O-Rings and FEP Face Seal Ring (Good to 400°F)					
<b>Options</b>	Pneumatic Level Transmitters calibrated to ranges below 50"WC					
<b>Process Connections:</b>	316L Stainless Steel SAN Flush Mount Weld-on Nipple included <b>LT-07-SAN</b>					
	316L Stainless Steel NPT Process connection Adapter, 1 1/2", 1" NPT M <b>LT-07-SAN-S (x")</b>					
<b>Dummy Plug:</b>	Stainless Steel Dummy Plug for PMC LT-07-SAN					<b>LT-11-SAN</b>
	<i>*Contact factory for custom Connections and Reducers.</i>					
<b>Example Ordering Format: PMC - LT/SAN - 300"WC - Si - Hc - HT</b>						