

DEPTH/LEVEL TRANSMITTER - RANGEABLE RS485 VERSALINE VL5XX6 SERIES WITH 4-20 MA AND TEMPERATURE OUTPUT

The PMC VersaLine VL5xx6 Series is part of a comprehensive range of submersible transmitters for the depth and level measurements of ground, surface, waste, and sea water. Suitable for small size bore holes, wells, dams, irrigation, sewage lift stations, rivers and oceanography.

Refer to VL5xx6 2-wire Data Sheet for Rangeable 4-20 mA Analog-only version.

TECHNICAL SPECIFICATIONS

Full Scale Ranges (Zero Based)	Any range from 0 - 40" WC to 0 - 1000 psi FS gauge or absolute <i>Any ranges or engineering units can be specified</i>
Accuracy - Pressure	$\leq \pm 0.1\%$ FS (≥ 7 psi FS) $\leq \pm 0.25\%$ FS (< 7 psi FS) <i>Combined linearity, hysteresis, repeatability & zero/span setting</i>
Accuracy - Temperature	$\pm 1.8^\circ$ F
Long Term Stability	0.1% FS/yr for pressure ranges above 30 psi. Prorated for ranges below 30 psi (under standard conditions).
Overpressure (Proof Pressure)	Full scale ranges up to 15 psi: 45 psi Full scale ranges 15 psi to 1000psi: $> 3 \times$ FS
Operating Temperature Range	25° to +125°F (-4° to 50°C)
Compensated Temperature Range	25° to +125°F (-4° to 50°C)
Temperature Effects - Standard 25° to +125° F	$\pm 1.5\%$ TEB for ranges ≥ 30 psi $\pm 2\%$ TEB for ranges 7 - 30 psi <i>Ranges < 7 psi Thermal Characteristics are prorated</i>
Total Error Band - Optional 25° to +125° F	$\pm 0.15\%$ for ranges ≥ 7 psi $\pm 0.3\%$ for ranges < 7 psi <i>Includes linearity, hysteresis, repeatability, thermal effects and zero/span set</i>
Supply Voltage (2-wire)	9-30 VDC power <i>Lightning Protection Option</i>
Output Signal	RS485 and 4-20 mA (pressure signal) RS485 (pressure and temperature signal with active compensation option)
Output at 4 mA and 20 mA	Adjustable between -5% FS and 105% FS
Span	Adjustable between 25% FS and 110% FS
Response Time	Adjustable: 30 ms, 100 ms, 1 s, 10 s (default 30 ms)
Interface - Box and Software	USB Converter 309-001 and software (101224) required for zero, span, response time adjustments, and re-ranging. <i>One converter needed for multiple transmitters</i>
Cable – up to 5000ft in single length	Polyurethane molded, vented cable with Kevlar
Housing	Titanium with 5-year corrosion warranty - standard <i>Stainless Steel option available (not available with FEP cable)</i>
Weight (excluding cable)	5oz (excluding cable)

Process Measure Control

Features

- $< \pm 0.1\%$ or $< \pm 0.25\%$ FS
- 0-40"WC to 0-1000psi
- RS485 (Modbus) 4-20mA /pressure
- Rangeable 4:1
- 1" diameter Titanium
five year warranty




Applications

- Tank Level
- Bore Holes
- Waste Water Plants
- Sewage Plants
- Surface Water

Contact

PMC Engineering LLC
11 Old Sugar Hollow Rd
Danbury, CT 06810
USA
sales@pmc1.com
Tel: 203-792-8686
Fax: 203-743-2051
www.pmc1.com

Represented by:



PMC Engineering adopts a continuous development program which sometimes necessitates specification changes without notice

Your depth and level specialists for Ground, Surface, Sea and Waste Water

PMC Configurator

VL x x x xx

Model Construction	0.95" diameter Depth	5
Housing Material	316L SS - option (unavailable with FEP cable)	1
	Titanium - 5 year warranty - standard	2
Electrical Connection	Polyurethane molded cable	1
	FEP cable (High Temp) - <i>contact factory</i>	7
	Cable length must be specified at the time of ordering.	
Electrical Configuration - Programmable	RS485/4-20 mA/pressure	6b
	RS485/pressure/temperature	6c
Additional Information Required	(1) Pressure Range including engineering units (2) Specify gauge or absolute (3) Active compensation (0.15% FS Total Error Band) <i>Standard compensation (1.5% FS) is default</i> (4) Lightning Protection Option if required (5) Converter 309-001 if required (6) 101224 Software if required	

Example Ordering Format: VL5216b - 10psig - 40' cable - Lightning Protection

RELATED PRODUCTS AND 4-20 MA ONLY VERSION

Please refer to 2-wire VL5xx6 Data Sheet for Rangeable 4-20 mA only version.


In addition PMC offers products such as the **VL4000** and **MTM3000** in 3/4" and $\varnothing 3/8$ " housing where space is at a premium. The **VL2000** provides an open face construction avoiding clogging or sludge build up in waste water and similar applications. Visit www.pmc1.com for details.

FOR ZERO MAINTENANCE



In order to reduce on-site maintenance PMC has developed the **MP 11** Moisture Protection Reference Volume. For vented gauge transmitters this provides total isolation from the atmosphere by using a custom bladder, while maintaining the high performance of the transmitter. Totally maintenance free. Please specify MP 11.

MECHANICAL DETAILS



ELECTRICAL DETAILS

Configuration	+V Supply	-V Supply	P output(4-20 mA)	RS485A (+)	RS485B (-)	Case Ground
Programmable	Red	Black	Yellow	Brown	White	Green

Process Measure Control

Sensors for

- Pressure
- Level
- Vacuum
- Humidity
- Temperature
- Force
- Position

Accessories

PMC offers a range of Accessories and variants for depth and level transmitters. Reference separate data sheet.

- Termination Enclosure
- Cable Hanger
- Moisture Protection
- Calibration Adaptor
- Sink Weights
- Level Meters

PMC is

- Engineering Driven
- Confidential
- Experienced
- Responsive
- Dynamic
- Friendly

Your depth and level specialists for Ground, Surface, Sea and Waste Water